

5742937871

2929

Form Approved
OMB No. 44-R1267

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME McMillan Music Company		EMERGENCY TELEPHONE NO. (215) 441-0212
ADDRESS (Number, Street, City, State, and ZIP Code) 1120 Jacksonville Rd, Ivyland, PA 18974		
CHEMICAL NAME AND SYNONYMS	TRADE NAME AND SYNONYMS CORK GREASE	
CHEMICAL FAMILY Petrolatum/Synthetic Wax/Tallow Blends	FORMULA Proprietary	

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Unit)	ALLOYS AND METALLIC COATINGS	%	TLV (Unit)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Unit)

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	N/A	SPECIFIC GRAVITY (M ₂ O-1)	
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT. VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (_____ "1)	
SOLUBILITY IN WATER	Nil		
APPEARANCE AND ODOR	White Paste/Wintergreen Scent		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	500° F.	FLAMMABLE LIMITS	Let	Uet
EXTINGUISHING MEDIA	Dry Chemical, CO₂, Foam, Sand, Earth, Water Fog			
SPECIAL FIRE FIGHTING PROCEDURES	Water is not a suitable extinguishing agent.			
UNUSUAL FIRE AND EXPLOSION HAZARDS	None			

5742937871

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-11387

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME McMillan Music Company		EMERGENCY TELEPHONE NO. (215) 441-0212
ADDRESS (Number, Street, City, State, and ZIP Code) 1120 Jacksonville Rd, Lyland, PA 18974		
CHEMICAL NAME AND SYNONYMS	TRADE NAME AND SYNONYMS CORK GREASE <i>TUNING SLIDE GREASE</i>	
CHEMICAL FAMILY Petrolatum/Synthetic Wax/Tallow Blends	FORMULA Proprietary	

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VENICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	N/A	SPECIFIC GRAVITY (M ₂ O=1)	
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (_____ =1)	
SOLUBILITY IN WATER	Nil		
APPEARANCE AND ODOR	White Paste/Wintergreen Scent		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	500° F.	FLAMMABLE LIMITS	Le	Uel
EXTINGUISHING MEDIA	Dry Chemical, CO2, Foam, Sand, Earth, Water Fog			
SPECIAL FIRE FIGHTING PROCEDURES	Water is not a suitable extinguishing agent.			
UNUSUAL FIRE AND EXPLOSION HAZARDS	None			