

AKA - TAYLOR BAND & ORCHESTRA SLIDE OIL

MATERIAL SAFETY DATA SHEET
MANUFACTURERS NAME: Players Music Co.
ADDRESS: 726 East Broadway, Mesa, AZ 85204
BUSINESS PHONE: 480-833-2500
NAME OF PREPARER: G.M. Westlund
DATE PREPARED: 7/17/04 (revised)

GENERAL			
TRADE NAME PLAYERS SLIDE OIL		TELEPHONE NUMBERS	
OTHER NAMES: Petroleum hydrocarbon		EMERGENCY: 1-800-424-9300 (CHEMTREC)	
CHEMICAL FAMILY See Above		DOT Hazardous Materials Proper Shipping Name Not DOT Regulated	
GENERIC NAME		DOT Hazard Class N/A	
CAS No.	Company	UN/NA ID No.	
Mixture	LD. No.	NONE	
II SUMMARY OF HAZARDS			
Physical Hazards:		Minor Eye & Skin Irritant	
Acute Health Effects:		Can cause mild irritation to body tissues.	
Chronic Health Effects:		None Known	
HMIS Rating:	Health: <input type="text" value="1"/>	Reactivity: <input type="text" value="0"/>	
	Fire: <input type="text" value="1"/>	Personal: <input type="text" value="H"/>	
(4=Severe, 3=Serious, 2=Moderate, 1=Slight, 0=Insignificant)			
III FIRE AND EXPLOSION			
Flash Point (Method)	Autoignition Temperature	Flammable Limits (%Volume in air)	
120° F. TCC	Unknown 660°F	Lower-	1.30%
		Upper-	9.8%@77°F.
FIRE AND EXPLOSION HAZARD	Combustible vapors can be released if the product is exposed to high temperature. Vapors can settle in low areas and travel some distance along the floor. Under normal conditions no hazard is expected.		
EXTINGUISHING MEDIA			
	Foam	<input checked="" type="checkbox"/>	Water Spray <input type="checkbox"/>
	CO2	<input checked="" type="checkbox"/>	Dry Chemical <input type="checkbox"/>
SPECIAL FIREFIGHTING PROCEDURES			
Keep containers cool with water spray. In case of fire, NIOSH/MSHA approved respirators and appropriate personal protection is recommended.			

MATERIAL SAFETY DATA SHEET

IV HEALTH HAZARDS				
INHALATION	Under normal conditions not expected to be a problem. Heat vapor concentrations >1000ppm can be irritating to eyes, cause central nervous effects, including headache, nausea, dizziness and unconsciousness.			
EYE CONTACT	Can cause irritation as any foreign body. Should not injure eye.			
SKIN ABSORPTION	Not expected to occur.			
SKIN IRRITATION	Prolonged direct exposure may cause mild skin irritation. Low order of toxicity.			
INGESTION	Can cause nausea and diarrhea. Small amounts of the product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury.			
SUMMARY OF CHRONIC HAZARDS AND SPECIAL HEALTH EFFECTS	None Known			
V PROTECTIVE EQUIPMENT AND OTHER CONTROL MEASURES				
RESPIRATORY	With proper ventilation none needed, however if misting applications put exposure above the safe level(TLV), a NIOSH approved respirator is recommended.			
EYE	Chemical Glasses			
SKIN	For sensitive skin chemical resistant gloves recommended.			
ENGINEERING CONTROLS	good ventilation.			
OTHER HYGIENIC AND WORK PRACTICES	Train employees in proper handling procedures in this section before allowing them to work with this product. Clean up spills immediately.			
VI OCCUPATIONAL EXPOSURE LIMITS				
Substance	CAS No.	EXPOSURE LIMITS IN AIR		
		ACGIH(TLV)	OSHA(PEL)	OTHER
Synthetic Isoparaffinic hydrocarbon	64742-48-9	400PPM	400PPM	
<p>NOTE: This product contains no levels of listed substances, which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute.</p>				

MATERIAL SAFETY DATA SHEET

EMERGENCY AND FIRST AID

INHALATION Using proper respiratory protection, remove affected victim from exposure. Administer artificial respiration if breathing has stopped. Call physician immediately.

EYE CONTACT Flush with water for at least 15 minutes. If irritation persists consult a physician.

SKIN CONTACT Wash exposed area. Remove contaminated clothing and wash before reuse.

INGESTION Do not induce vomiting. Keep at rest. Call Physician immediately. Never give anything to an unconscious person.

EMERGENCY MEDICAL TREATMENT PROCEDURES

VIII SPILL AND DISPOSAL

PRECAUTION IF MATERIAL IS SPILLED OR RELEASED Stop leak. Dam up area of spill. Dry floor with absorbant, Shovel into metal or plastic lined containers. Keep area clear of traffic as the floor will be extremely slippery. Clean area with usual floor cleaner.

WASTE DISPOSAL METHODS DISPOSE ACCORDING TO LOCAL, STATE & FEDERAL REGULATIONS.

IX COMPONENTS (this may not be a complete list of components)

Component Name	CAS No.	Hazardous Component Advisory	Composition Amount-(WT)
Synthetic isoparaffinic hydrocarbon	64742-48-9	#1	80-99%

#Listed by: 1-OSHA(air) 2-OSHA(regulated substance) 3-NTP(carcinogens) 4-ACGIH(chemicals) 5-IARC(human carcinogens) 6-DOT hazardous materials

** RQ-1000#(reportable quantities)
 *** RQ-5000#(reportable quantities)
 *SARA Title III

MATERIAL SAFETY DATA SHEET

X	PHYSICAL AND CHEMICAL DATA		
Boiling Point >350°F	Viscosity Units, Temp. (Method) N/AP		Dry Point
Freezing Point -75°F	Vapor Pressure Unknown		Volatile Characteristics
Specific Gravity (H ₂ O=1) 08 +/-0.5	Vapor Density (Air=1 @60-90°F) Unknown		Stable X Unstable
Solubility in Water slight	pH -conctrte 6.0-7.0 pH -dilute	Hazardous Polymerization Will Not Occur	
Other Physical and Chemical Properties		Evaporation Rate <water	
Appearance and Odor	Clear liquid, pleasant odor.		
Materials to Avoid	Strong Oxidizing Agents.		
Conditions to Avoid	Open flames, excessive heat		
Hazardous Decomposition Products	Carbon Dioxide, Carbon Monoxide		
XI	ADDITIONAL PRECAUTIONS		
HANDLING, STORAGE AND DECONTAMINATION PROCEDURES	Keep container closed when not in use to avoid contamination.		
GENERAL COMMENTS:			
<p style="text-align: center;">DISCLAIMER OF LIABILITY</p> <p>The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling storage, use or disposal of the product.</p>			